



The Seac Banche Orion is designed to simplify the processing of cheques and other documents at the point of presentation.

This unique reader scanner is the logical development to provide the functionality and performance normally found in devices too big for modern teller positions in a unit with the same footprint of a check reader.

The easy-to-use Orion brings to the quality of image capture and read performance of the SB 1500 the benefits of additional flexibility and automatic feeding, allowing tellers to devote their attention to the customer rather than to manually feeding the documents. This capability is particularly valuable when transactions with several cheques or documents are presented. A wide range of options - including colour imaging, voiding/ endorsing functionalities and card management - further enhance its flexibility and broaden its scope of use.



PAPER HANDLING

Autofeeder with a capacity of up to 35* documents Double feed control

Output stacker: capacity approx. 35* documents

Transport speed: 560 mm (22")/sec

Throughput options: drop feed, 65 dpm, 130 dpm



Width: 100 to 225 mm (3.94" to 8.86") Height: 52 to 108 mm (2.05" to 4.25") Weight: 70 to 120 g/sqm (18.7 to 32 lbs)



MICR: magnetic fonts CMC7 and E13B OCR (optional): optical fonts OCR-A, OCR-B, OCR A-B, OCR alphanumeric, E13B

Barcode reading (optional)

Additional deco capabilities (2D barcode, multiple

snippets - optional)

IMAGE CAPTURE

Front and rear images in one pass (duplex) Red dropout imaging available 200 x 200 dpi or 100 x 100 dpi Higher resolution available for 2D barcode deco-

256 or 16 grey levels or colour 64K (optional)

IMAGE FORMAT

Bitmap, Jpeg, Tiff, G4 (B/W)

Seac Banche S.p.A. Headquarter

Via Francesco Petrarca, 14 - 50041 Calenzano (FI), Italy Tel.: +39 055.8870700 - Fax: +39 055.8873646

E.Mail: info@seacbanche.com - Web site: www.seacbanche.com

INTERFACE

USB 2.0

RS-232 (codeline reader emulation)

API SOFTWARE TOOLS

Designed for MS Windows XP Available for MS Windows 2000, 95/98/ME Vista

DIMENSIONS

Length: 260 mm (10.2") Width: 120 mm (4.7") Height: 180 mm (7.1") Weight: 1.7 Kg (3.7 lbs)

COMPONENT

Antifraud feature by UV light

Rear Inkjet Printer (optional)

Programmable endorser, application controlled High-capacity cartridge, 1-line, 96 dpi Line of data can extend to full width of document

Front Stamp (optional)

Self-inking cancellation stamp

Max. dimensions: 22 x 16 mm (0.6 x 0.9")

Magnetic badge reader (optional)

Manual swipe reader Tracks 1&2 or 2&3

Chip memory card (optional)

"Dip" reader/writer integrated in the reader scanner (Not available)

Secure Digital card (optional)

For image/data storage in stand-alone operation (Not available)

* depending on the paper's thickness.

depending on the length of the document.

